



BASKET REMOVE (A)

NB	L	H	H1	A	E		T	
					P.C.D	HOLE NOS.		
25NB	160	165	106	270	79.5	16	4	3.5
40NB	200	205	120	320	98.5	16	4	3.5
50NB	230	213	126	340	121	19	4	4
80NB	310	314	151	460	152	19	4	4
100NB	350	324	162	500	190	19	8	4

NOTE:-
 ALL DIMENSION ARE IN mm
 FLANGE CONNECTION AS PER ANSI B16.5 # 150 RF
 TEMPERATURE RESISTANCE PFA-200°C & FEP-180°C

CLASS-150	PRESSURE RATING		SPARK TEST
	BODY	SEAT	
	30 kg/cm ²	22 kg/cm ²	15 kVA

13	BOLT,NUT&WASHER	MS/SS	08
12	RING BOLT	MS/SS	01
11	ROUND CORD	PTFE	01
10	SEAL RING	PTFE	01
09	FILTER BASKET	PTFE	01
08	ANTI-TORSION INSERT	PTFE	01
07	FILTER BASKET SUPPORT	PTFE	01
06	FILTER WEB	ETFE	01
05	COVER DISC	PTFE	01
04	TRANSITION COVER	G.C. WITH LINED	01
03	TOP COVER	G.C	01
02	BOTTOM COVER	G.C. WITH LINED	01
01	VALVE BODY	G.C WITH LINED	01
SR.	DESCRIPTION	MATERIAL	QTY

KNS BASKET STRAINER F/END

SIGN	DATE	DRG. NO. :-
HBP	16/4/08	KNS/BS/0809-4
SJM	16/4/08	
JKS	16/4/08	

DRN.BY: HBP 16/4/08
 CHECK BY: SJM 16/4/08
 APPD.BY: JKS 16/4/08
 SCALE: NTS

KNS Lined Products Pvt Ltd