



NOTE:-

ALL DIMENSION ARE IN mm
 INLET FLANGE CONNECTION AS PER YOUR REQUIRE
 OUTLET FLANGE CONNECTION AS PER ANSI B16.5 #150 R/F
 TEMPERATURE RESISTANCE PFA-200°C & FEP-180°C
 ** MARK UNDER DEVELOPMENT
 *** MARK AS PER REQUIRE

PRESSURE RATING		SPARK TEST
CLASS-150	BODY 30 kg/cm ²	SEAT 22 kg/cm ² 15 KVA DC

15	NUT,WASHER	MS/SS	01
14	HAND WHEEL	GC	01
13	GRUB SCREW	MS	01
12	YOKE BUSH	GM	01
11	STUD,NUT,WASHER	MS/SS	04
10	GLAND PACKING	PTFE	---
09	GLAND PLATE	MS	01
08	GLAND BUSH	MS/SS	01
07	PLUG	MS WITH LINED	01
06	BONNET	G.C	01
05	SPRING WASHER	MS/SS	---
04	ALAN KEY BOLT	MS/SS	---
03	SEAT RING	PTFE	01
02	TOP PLATE	GC WITH LINED	01
01	VALVE BODY	GC WITH LINED	01
SR	DESCRIPTION	MATERIAL	QTY

KNS FLUSHBOTTOM VALVE #150 F/END

SIZE OUT-IN	A	B	C	D	E		F	G	H	I	J	K		L	M	N
					PCD	HOLE NOS						PCD	HOLE NOS			
25X40
40X50
50X80	75	32	127	190.5	152	93	48	19	4	121	19	4	200	475
80X100	100	36	157	229	190.5	127	75	19	4	152.4	19	4	250	564
100X150	152	48	209	280	229	157	100	19	4	190.5	19	8	250	722

DRN.BY HBP 16/4/08
 CHECK BY SJM 16/4/08
 APPD.BY JKS 16/4/08
 SCALE NTS
 DRG. NO. :- KNS/FBV/0809-5
KNS Lined Products Pvt Ltd