



BASKET REMOVE (A)

NB	L	H	H1	A	E		T	
					P.C.D	HOLE NOS.		
25NB	160	165	106	270	79.5	16	4	3.5
40NB	200	205	120	320	98.5	16	4	3.5
50NB	230	213	126	340	121	19	4	4
80NB	310	314	151	460	152	19	4	4
100NB	350	324	162	500	190	19	8	4

NOTE:-
 ALL DIMENSION ARE IN mm
 FLANGE CONNECTION AS PER ANSI B16.5 # 150 RF
 TEMPERATURE RESISTANCE PFA-200°C & FEP-180°C

CLASS-150	PRESSURE RATING	SPARK TEST
	BODY	15 kVA
	30 kg/cm ²	

S.R.	DESCRIPTION	MATERIAL	QTY
01	VALVE BODY	D/CS/SS WITH LINING	01
02	BOTTOM COVER	D/CS/SS WITH LINING	01
03	TOP COVER	D/CS/SS WITH LINING	01
04	TRANSITION COVER	D/CS/SS WITH LINING	01
05	COVER DISC	PTFE	01
06	FILTER WEB	ETFE	01
07	FILTER BASKET SUPPORT	PTFE	01
08	ANTI-TORSION INSERT	PTFE	01
09	BASKET	PTFE/FEP/PVDF	01
10	SEAL RING	PTFE	01
11	ROUND CORD	PTFE	01
12	RING BOLT	SS	01
13	BOLT,NUT&WASHER	SS	08

KNS BASKET STRAINER F/END

DRN.BY	HBP	DATE	16/4/08
CHECK BY	SJM	DATE	16/4/08
APPD.BY	JKS	DATE	16/4/08
SCALE	NTS		

DRG. NO :- KNS/BS/0809-4

KNS Lined Products Pvt Ltd