



SIZE	A	B	C	D	E		F	T	
					P.C.D.	HOLE NOS.			
25NB	127	25	51	108	79.5	16	4	11.2	3.5
40NB	165	40	73	127	98.5	16	4	14.2	3.5
50NB	178	50	92	152	121	19	4	16	4
80NB	203	75	127	191	152	19	4	19	4
100NB	229	100	157	229	190	19	8	24	4

NOTE:-

ALL DIMENSION ARE IN mm

FACE TO FACE DIMENSION AS PER ANSI.B16.10

FLANGE CONNECTION AS PER ANSI B16.5 # 150 RF

TEMPERATURE RESISTANCE PFA-200°C & FEP-180°C

PRESSURE RATING		SPARK TEST
CLASS-150	BODY 30 kg/cm <sup>2</sup>	INDICATOR 22 kg/cm <sup>2</sup>
		15 kVA

06	STUD,NUT&WASHER	SS	04
05	GASKET	PTFE	02
04	INDICATOR	TOUGHENED GLASS	02
03	BOTTOM PLATE	D/CS/SS	01
02	TOP PLATE	D/CS/SS	01
01	BODY	D/CS/SS WITH LINING	01
SR.	DESCRIPTION	MATERIAL	QTY

SIGHT GLASS ASA-150# F/END



SIGN DATE

DRN.BY HBP 24/4/08

DRG. NO. : KNS/SGI/0809-7

CHECK BY SJM 24/4/08

APPD.BY JKS 24/4/08

SCALE NTS

**KNS Lined Products Pvt Ltd**