



SIZE	A	B	C	D	E		T		
					P.C.D. HOLE	NOS.			
25NB	127	25	51	108	79.5	16	4	11.2	3.5
40NB	165	40	73	127	98.5	16	4	14.2	3.5
50NB	178	50	92	152	121	19	4	16	4
80NB	203	75	127	191	152	19	4	19	4
100NB	229	100	157	229	190	19	8	24	4

NOTE:-

ALL DIMENSION ARE IN mm

FACE TO FACE DIMENSION AS PER ANSI.B16.10

FLANGE CONNECTION AS PER ANSI B16.5 # 150 RF

TEMPERATURE RESISTANCE PFA-200°C & FEP-180°C

PRESSURE RATING		SPARK TEST	
CLASS-150	BODY	SEAT	15 KVA DC
	30 kg/cm ²	22 kg/cm ²	

06	STUD, NUT & WASHER	MS/SS	04
05	GASKET	ASBESTOS	02
04	GLASS INDICATOR	TOUGNED	01
03	BOTTOM PLATE	G.C	01
02	TOP PLATE	G.C.	01
01	BODY	G.C/C.S/S.S. WITH LINED	01
SR.	DESCRIPTION	MATERIAL	QTY

SIGHT GLASS INDICATOR ASA-150# F/END

KNS

DRG. NO :- KNS/SGI/0809-7

DRN. BY	HBP	DATE
CHECK BY	SJM	24/4/08
APPD. BY	JKS	24/4/08
SCALE	NTS	

KNS Lined Products Pvt Ltd